


SIRIUS

**HL45
Alcohol -
Resistant
Resin**



THERMAL TRANSFER RIBBONS



TTR Properties

Base Film Thickness	$4.5 \pm 1.0\mu$
Total Thickness	$7.0 \pm 1.0\mu$
Ink Color	Black
Ink Melting Point	94°C
Maximum Print Speed	150 mm / second


Receiving Materials

Synthetics
Films

Polypropylene & Polyester
PET

Resistance

Scratch	Very Good
Smear	Very Good
Chemical	Good
Alcohol	Excellent
Heat	Good
Water	Excellent



Dynic USA Corporation
4750 N.E. Dawson Creek Drive
Hillsboro, Oregon 97124
Phone (800) 326-1249
(503) 693-1070
Fax (503) 648-1185
www.dynic.com

Notes:

1. This chart shows Dynic USA Corporation's HL45 Alcohol-Resistant Resin formulation on typical receiving materials.
2. Dynic USA recommends that the ribbon be tested independently to match specific label requirements, and in order to determine optimum print conditions and speed.
3. Test results may vary depending on label and printing conditions.
4. Storage: 5° to 35°C; 30 to 85% RH. Shelf Life: 1 Year.
5. Dynic USA Corporation reserves the right to change any Dynic product specifications without prior notice, provided there is no change in product performance.