



THERMAL TRANSFER RIBBON
TECHNICAL DATA SHEET


FTX403X

Standard Near Edge Wax/Resin

Product Description

FTX403X is Fujicopian's standard wax-resin product for near edge printers that offers high print performance at a more economical price. FTX403X is specifically to designed to be a versatile performance product that can be used in applications from paper labels to plastic films. FTX403X offers excellent sensitivity and high speed printing capability (tested to 28ips).

Rader Chart



*Performance above are rated being compared among the near edge wax/resin categories of Fujicopian FTX400 series.

Product Specifications

Description
Ink Type
Total Thickness
Base Film Thickness
Ink Thickness
Melting Point
Print Speed
Print Density

Specification
Wax/Resin
6.8 +/-0.5 Micrometer
4.5 +/-0.5 Micrometer
2.3 +/-0.5 Micrometer
65°C
up to 10 ips

1.60 Densitometer*Print density depends on print conditions.

Applications

- Shipping Labels
- Storage Labels
- Retail Tags
- Pharmaceutical Lables
- Flexible Package Labels
- Outdoor

Recommended Label Stock

- Matte Paper
- Coated Paper
- Synthetic Paper
- Polvolefin
- Polyester
- Polypropylene
- Polyethylene

Storage Conditions

- Temperature: 5 to 35° C (41 to 95F)
- Humidity: 45 to 85 % RH
- Keep away from direct sunlight., high temperature and humidity.

NORTH & SOUTH AMERICA FUJI COPIAN (USA), INC.

PO Box 1118 1214 State Highway 34E Winnsboro, SC 29180 U.S.A. TEL +1-803-635-9799 , 1-800-441-3854 FAX +1-803-635-1000

E-mail: info@fujicopianusa.com Website: http://www.fujicopianusa.com

EUROPE & AFRICA FUJI COPIAN (U.K.) LTD.

Bailey Court, Bailey Drive
Gillingham Business Park
Gillingham, Kent ME8 0PZ England
TEL +44-1634-371137
FAX: +44-1634-366560
E-mail: sales@fujicopian.co.uk
Website: http://www.fujicopian.co.uk

ASIA-PACIFIC FUJICOPIAN CO., LTD.

Tokyo Branch Kamei Bldg., 2-17-13 Kiba, Koto-ku, Tokyo 135-8525 Japan TEL +81-3-3642-0371 FAX +81-3-3642-0610 E-mail: info@fujicopian.com Website: http://www.fujicopian.com